


Acpi Asus010 1010100 Drivers

1.9 Jumpers

Clear RTC RAM (3-pin CLRRTC)

This jumper allows you to clear the Real Time Clock (RTC) RAM in CMOS. You can clear the CMOS memory of date, time, and system setup parameters by clearing the CMOS RTC RAM data. The onboard button cell battery powers the RAM data in CMOS, which includes system setup information such as system passwords.



P8H61 Series Clear RTC RAM

To erase the RTC RAM:

1. Turn OFF the computer and unplug the power cord.
2. Move the jumper cap from pins 1-2 (default) to pins 2-3. Keep the cap on pins 2-3 for about 5-10 seconds, then move the cap back to pins 1-2.
3. Plug the power cord and turn ON the computer.
4. Hold down the key during the boot process and enter BIOS setup to re-enter data.

Except when clearing the RTC RAM, never remove the cap on CLRRTC jumper default position. Removing the cap will cause system boot failure!

- If the steps above do not help, remove the onboard battery and move the jumper again to clear the CMOS RTC RAM data. After clearing the CMOS, re-install the battery.
- You do not need to clear the RTC when the system hangs due to overclocking. For system failure due to overclocking, use the CPU Parameter Recall (C.P.R.) feature. Shut down and reboot the system; then the BIOS automatically reverts parameter settings to default values.

DOWNLOAD: <https://tinurli.com/292e33>



7c23cce9bc

Related links:

[ORPALIS PaperScan Professional 3.0.88 With Crack nihongosomatoment4pdf20](#)
[Pegatron Apx1dm Drivers](#)
[Excuse Me Sir It Appears That Someone Is Endeavour girls camaron tunes](#)
[Eiraag kannada full movie mp4 free download](#)